



**Double Barn Door Track Required Information**

- Proper header must be installed for full length of track.
- We recommend a flush pull on interior side of door. If an interior grip is desired verify adequate clearance in open position.

Provide the following information in order to receive a customized drawing for client final approval. \* (Required Field)

- \* 1. Door Thickness \_\_\_\_\_
- 2. Door Height \_\_\_\_\_
- \* 3. Door Width \_\_\_\_\_
- \* 4. C to C distance of roller brackets (typically centered on door stile) \_\_\_\_\_
- \* 5. Door travel: Both doors (max. travel for each door should be 1" less than door width to ensure door does not come off floor guide) \_\_\_\_\_
- 6. Clearance between door and mounting surface (see Detail A, 1" unless otherwise specified (3/8" minimum)) \_\_\_\_\_
- 7. Center line of mounting brackets to top of door (See Detail A, 2 1/2" unless otherwise specified (2 1/8" min, 3 1/2" max)) \_\_\_\_\_

**Note to determine overall track length:**

\_\_\_\_\_ + \_\_\_\_\_ + \_\_\_\_\_ + 7 INCHES = \_\_\_\_\_ OVERALL TRACK LENGTH

LINE #4 (x2)                      LINE #5                      (LINE #3 - LINE #4)

